

### Albatros - Senkepumper 4" - modeller



Model	Hk	Kw	Amp 230V	Amp 400V
A13 M	0.50	0.37	3,9	
A13 M 2-wire	0.50	0.37	4.1	
A13 T	0.50	0.37	1,9	1,1
A19M	0.75	0.55	5.9	
A19 M 2-wire	0.75	0.55	5.8	
A19 T	0.75	0.55	2.8	1,6
A26 M	1.00	0.75	7.3	
A26 M 2-wire	1.00	0.75	7.3	
A26 T	1.00	0.75	3.5	2,0
A38 T	1.50	1,10	4.9	2,8
B10 M	0.75	0.55	5.9	
B10 M 2-wire	0.75	0.55	5.8	
B10 T	0.75	0.55	2.8	1,6
B14 M	1.00	0.75	7.3	
B14 M 2-wire	1.00	0.75	7.3	
B14 T	1.00	0.75	3.5	2,0
B20 T	1.50	1.10	4.9	2,8
B28 T	2.00	1.50	6.7	3,9
C14 T	1.50	1.10	4.9	2,8
C18 T	2.00	1.50	6.7	2,8
C27 T	3.00	2.20	9.5	5,5
D8 T	1.00	0.75	3.5	2,0
D12 T	1.50	1.10	4.9	2,8
D16 T	2.00	1.50	6.7	3,9
D24 T	3.00	2.20	9.5	5,5
D32 T	4.00	3.00	13.0	7,5
D44 T	5.50	4.00	17.2	9,9
F8 T	2.00	1.50	6.7	3,9
F13 T	3.00	2.20	9.5	5,5
F23T	5.50	4.00	17.2	9,9
G8 T	3.00	2.20	9.5	5,5
G15 T	5.50	4.00	17.2	9,9
G20 T	7.50	5.50	21.8	12,6